



- **10.4" TFT LCD LED Backlight**
- **Resolution SVGA (800x600)**
- **PAL/NTSC Video Inputs**
- **Rugged Machined Aluminium casing**
- **Secure rear mount fixings**
- **Built-In Test Pattern output**
- **Text and graphics overlay capability**

The AV6011-104-RM1 is an SVGA PAL/NTSC display monitor for command and control consoles. The unit has a black bezel that allows the unit to be mounted behind an aperture window. It has a built in test pattern generator which can be used to loop back into the unit for test purposes. The enclosure is milled from a single aluminium block to ensure a rugged assembly.

An RS232 Command Link allows a Host controller to communicate with the display to add text and graphics overlay capability.

The RM1-T variant allows touch screen capability to be included in the system, touch commands are relayed to the host via command link.

Directives

2004/108/EC

2011/65/EU

Standards

BS EN 55022:2006+A2:2010 (CISPR 22:2005, Class B)

BS EN 55024:1998+A2:2003

Technical Specifications

Display	
Panel Size	10.4" diagonal
Resolution	SVGA (800 x 600 pixels)
Brightness	400cd/m ² (max)
Contrast Ratio	700:1
Response	30ms (Typical, Rising + Falling)
Viewing Angle	Horizontal ± 80° and Vertical + 60° to - 80° with CR = 10
Aspect Ratio	4:3
Colours	16.7M colours, 262K
Backlight Technology	LED
Surface Treatment	Anti-glare, Hardness 3H
Video Inputs	
Analogue	1x PAL/NTSC
Video Outputs	
Analogue	1x PAL Test Pattern
Optional Inputs / Outputs	
Brightness Control	Via MIL-DTL 38999 (0-100%)
Contrast Control	Via MIL-DTL 38999
Command Link	RS232 via MIL-DTL 38999
Connectors	
	MIL-DTL 38999 (62GB-12E16-26PN)
	2xBNC (Video Input and Output)
Mechanical	
Weight (Approx.)	2.7Kg
Dimensions	286mm x 216mm x 48mm (Excludes rear handle)
Bessel Finish	DEF STAN 80-161 Matt Black
Fixings	14 x M5
Environmental	
Humidity	95% RH @ +40°C
Protection Rating	IP61
Temperature	Operating Temperature: 0°C to +60°C
	Storage Temperature: -30°C to +85°C
	Cooling: No Moving Parts. Passive
Power	
	Input Voltage: 5V and 12V
	Power Consumption: 12W (5V @ 1.7A; 12V @ 0.32A)
Warranty	
	1 Year (extendable to 3 and 5 years)

Note:

The information in this document is subject to change without notice and should not be construed as a commitment by Advanced Vision Technology (AVT). While reasonable precautions have been taken, AVT assumes no responsibility for any errors that may appear in this document. Product images are indicative and may differ from the final product.