



- **15" TFT LCD LED Backlight**
- **Resolution XGA (1024x768)**
- **Def Stan 00-82 Vetronics Infrastructure for Video Over Ethernet (VIVOE)**
- **Available with GigE Vision capability**
- **Generic Vehicle Architecture (GVA) compatible**
- **Two PAL or NTSC analogue inputs**
- **Picture in Picture, Matrix and video scaling**
- **1000baseT Ethernet**
- **Customisable Overlay**
- **Programmable Edge Keys**
- **Touch Screen**

The VDS1500 is a ruggedised display fully compatible to generic vehicle architecture requirements. It features a display with a native display resolution of 1024 x 768.

The display has an integrated resistive touch panel and has GVA Human Machine Interface layout which conforms to Def Stan 00-25. Twenty programmable function keys are available which can be fully customised.

The VDS1500 is unique in a way that not only can it receive upto to 4 full PAL or NTSC digital streams via its 1000baseT Ethernet port it can also encode and transmit the two attached analogue video inputs into a digital Def Stan 00-82 stream to be received by other displays or a central recording system. Tile and display upto 16 video inputs with reduced resolution.

Video input streams both digital and analogue can be scaled and presented in either a matrix or picture in picture format.

The display enclosure is manufactured out of a solid piece of milled aluminium to withstand the most demanding environments across a wide range of operational conditions.

Technical Specifications

Display	
Panel Size	15" diagonal
Resolution	XGA (1024 x 768 pixels)
Brightness	600cd/m ² (max)
Contrast Ratio	700:1
Response	25ms (Typical, Rising + Falling)
Viewing Angle	Horizontal and Vertical $\pm 70^\circ$ with CR = 10
Colours	16.7M colours, 262K
Backlight Technology	LED
Touchscreen	
Technology	Resistive
Control	USB/RS232
Video Inputs	
Analogue	2 PAL or NTSC
Digital	Up to 4 (4 Full PAL or NTSC format)
Video Outputs	
Digital	2 Encoded DefStan 00-82 streams
Bezel Keys	
	20 function keys
	GVA Dedicated keys (Def Stan 00-25)
	Up/Down (Dimmable LCD Backlight Operation)
	Power Button
	FWD camera
	Dimmable membrane backlight (Optional)
Optional Inputs / Outputs	
Communications	USB, RS232, Gigabit Ethernet
General Purpose	8 (TTL / LVTTTL)
Connectors	
	Amphenol Rugged MIL Standard Connectors (MIL-DTL 38999/3)
Mechanical	
Weight (Approx.)	6Kg
Dimensions	309mm(W) x 270mm(H) x 66.8mm(D)
Environmental	
Humidity	90% @ +40°C noncondensing
Ingress Protection	IP65
Temperature	Operating Temperature: -20°C to +50°C
	Storage Temperature: -30°C to +80°C
	Cooling: No Moving Parts. Passive
	Optional Extended Temperature Range (-46°C to +70°C)
Power	
	Input Power Voltage: 16-40V (28V Typical)
	Isolated DC/DC Converter (MIL-STD-1275 & MIL-STD-704)
	EMI & Transient Filter (DefStan 61-5)

Please Note:

The information in this document is subject to change without notice and should not be construed as a commitment by Advanced Vision Technology (AVT). While reasonable precautions have been taken, AVT assumes no responsibility for any errors that may appear in this document. Product images are indicative and may differ from the final product. © Advanced Vision Technology 2015